

KM-2035

► print ► copy ► scan ► fax

THE EFFICIENT A3 WORKGROUP COPIER WITH CONNECTIVITY



- 20 pages per minute in A4, 10 pages per minute in A3
- Optional host-based printer functionality
- 350 sheets input as standard, maximum 1,250 sheets
- Time to first copy: 5.9 seconds from power on
- 32 MB RAM for full digital functionality including scan-once-print-many
- Optional duplex document processor for up to 50 sheets
- Long-life components, easy maintenance

Product depicted includes optional extras

Buy a copier today, get a printer tomorrow - it's possible with the Kyocera KM-2035. Numerous digital copy functions and a wide range of clever options make the KM-2035 the ideal A3 copier for workgroups. One of those options is the printing system that turns the KM-2035 into an affordable printer. And thanks to the KM-2035's long-life components, you can benefit from its functionalities at very low running costs. The Kyocera KM-2035: a secure investment for your office!

 **KYOCERA**

KM-2035

Monochrome A3 multifunctional

The KM-2035 incorporates extremely durable components that guarantee smooth and reliable operation. The system is designed to last for extremely long hardware maintenance cycles. Thus the KM-2035 keeps your overall operating costs low and productivity high – at the same time ensuring a minimum impact on the environment.

GENERAL

Technology: Kyocera Laser, Mono component
Type: Desktop
Engine speed: Max. 20/10 pages per minute A4/A3
Resolution: 600 dpi x 600 dpi, 256 greyscales
Time to first copy: 5.9 seconds or less
Warm-up time: 20 seconds or less
Duty cycle: Max. 30,000 sheets per month
Power source: AC 220 ~240 V, 50/60 Hz
Power consumption: Copying: 461 W, Stand-by: 104 W, Power saving (ECOpower): 43 W
Noise (ISO 7779): Copying: 64 dB (A), Stand-by: 40 dB (A)
Power saving (ECOpower): Immeasurably low
Dimensions (W x D x H): 574 x 552 x 502 mm
Weight: Main unit: Approx. 39 kg
Certification: GS/TÜV/CE
This product is produced according to the quality norm ISO 9001 and the environmental guidelines ISO 14001

PAPER HANDLING

All mentioned paper capacities are based on a paper thickness of max. 0.11 mm. Please use paper recommended by Kyocera under normal environmental conditions.

Input capacity: 300-sheet universal feeder, 64-105g/m², A3, A4, A5, Ledger, Letter, Legal, Folio, 50-sheet multi-purpose tray, 45-160g/m², A3, A4, A5, Ledger, Letter, Legal, Folio, Custom (98 x 147 - 297 x 432 mm) Max. 1,250 sheets (4 paper feeders)
Output capacity: 250 sheets face-down

COPY FUNCTIONS

Max. original size: A3
Continuous copy: 1 - 999 copies
Memory capacity: 32 MB standard, 18 MB of bitmapping memory and 14 MB of image storage memory
Max. 160 MB, 1 slot (16, 32, 64, 128 MB DIMM)
Zoom range: 25 - 400% in 1% steps
Digital copy features: Scan-once-print-many, electronic sort copy, rotate sort copy, automatic paper selection, duplex copying*, combined inch/metric copying, N-up copy (2-in-1, 4-in-1), ECOcopy mode, program key mode, auditory signals, management mode
* additional duplex unit DU-410 is required
Exposure mode: Auto, Manual: 5 or 9 steps
Image adjustments: Text + Photo, Text, Photo

CONTROLLER PRINT FUNCTIONS (OPTIONAL)

Processor: ARM 946-S 150 MHz, FlexRISC
Memory: Standard 32 MB, max. 32 MB
Emulations: Host-based printing system for Windows 98, ME, 2000, XP

INTERFACE

Standard interface: USB 2.0 (Hi-Speed)

OPTIONS

Paper handling
DP-410 Duplex Document Processor:
50-sheet, Duplex scan, 45-160g/m², A3-A5R, Folio, Ledger, Statement R
PF-410 Paper Feeder:
300 sheets, 60-105g/m², A3-A5R, Folio, Ledger, Statement R (up to three PF-410 can be added to the standard configuration)
DU-410 Duplex Unit:
60-80g/m², A3-A5R, Folio, Ledger, Statement R

Memory: Max. 160 MB, 1 slot (16, 32, 64, 128 MB DIMM)
External network interface: IB-110 Ethernet print server: 10Base-T/100Base-TX

Others
Platen cover (D): Platen cover

Cabinet
Wooden / metal desk with storage capacity including castors (wheels)
CB-410 (high / wooden)
CB-415 (low / wooden)
CB-411 (high / metal)
CB-416 (low / metal)

KM-NET VIEWER

KM-NET VIEWER is an advanced network management software tool that is compatible with all Kyocera printers and multifunctional products as well as those of other vendors by using the standardized protocol SNMP. The settings of all print devices on the network can be checked visually and amended from any Windows PC. KM-NET VIEWER also acts as a valuable, real-time early warning system by sending e-mail messages to users/administrators.

CONSUMABLES

TK-410 Toner Kit: Microfine toner for 15,000 pages with 6% A4 coverage

Capacity of starter toner is 3,000 pages with 6% A4 coverage



Select your options to suit your needs:

DP-410 Duplex document processor

DU-410 Duplex unit

PF-410 Paper feeder



Product depicted includes optional extras

Your Kyocera Business Partner:

Kyocera Mita Europe B.V., Hoeksteen 40, 2132 MS Hoofddorp, The Netherlands,
Tel +31 (0) 20 65 40 000, Fax +31 (0) 20 65 31 256, www.kyoceramita-europe.com

KM-2035- English - 8DSE2035. Kyocera Mita does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.

